


# MAX dp 201C

**NEW**



MADE IN ITALY

WARRANTY YEARS  
**2**



The Inverter Welding Power Source MAX® dp 201C developed by STEL concentrates high performance for MMA and Tig welding with the most stringent safety requirements for the work place.

Advanced Technology owing to the use of the DSP (Digital Signal Processor) that controls all the inverter signals. V.R.D., TIG lift and variable slope down features, satisfy the requirements of every work place.

## MAIN FEATURES



### PULSE

The function of Tig pulse (up to 999 Hz) and electrode (innovated Arc Pulsing from 0.4 to 5 Hz) make this MAX® dp 201C a unic product.



### TIG LIFT

Using a Tig Torch with gas-valve, the MAX® dp 201C can perform excellent DC TIG welding with Lift-Arc-Ignition and variable Slope Down



### CELLULOSIC ELECTRODE

Thanks to his inverter the MAX® dp 201C is able to weld any kind of electrode, including the hard and difficult 6010 and Citoflex.



### VRD (VOLTAGE REDUCTION DEVICE)

which is the reduction of the OCV across the + and - terminals at a safety level below 20V, in order to avoid Electrical Shocks.



### FLY-BACK

Advance dynamic electronic system of auxiliary input voltage (not traditional transformer) masters total control from all input power source voltages automatically.



### STICK MODE (MMA)

Variable Arc Force and Hot Start features assist perfect welding performance.

Technical Data	MAX® dp 201C	Features	MAX® dp 201C
Main Voltage	230/240 V	Earth Clamp	25 mm <sup>2</sup>
Phase	1	Degree of Protection	IP 23
Frequency	50/60 Hz	Insulation Class	H
Real Current (20%)	19 A	Cooling	Air
Real Power (20%)	4,4 KVA	Work Temperature	40°C
Power Factor	0,8	Length/Width/Height (mm)	330x135x270
No Load Voltage	25-100 V	Weight	6,8 Kg
Current Range	4-200 A		
Welding Current 45% (25°C)	200 A		
Welding Current 100% (25°C)	160 A		
Welding Current 20% (40°C)	200 A		
Welding Current 60% (40°C)	160 A		
Welding Current 100% (40°C)	140 A		

The date is measured at an environment temperature of 40 °C

### Main Accessories



**WELDING KIT 25mm<sup>2</sup>**  
 - Earth Cable 3m 25mm<sup>2</sup> Rubber  
 - Cable/Electrode Holder 4m 25mm<sup>2</sup> Rubber  
 - Wire Brush/Chipping Hammer+Handscreen  
 Cod. 6006610010



**HELMET MEGA 600S**  
 Large viewing area for maximum vision featuring innovative adjustments of delay, sensitivity and DIN protection, Shade 9-13.  
 Cod. 601253000L



**CABLES KIT 25mm<sup>2</sup>**  
 - Earth Cable 3m 25mm<sup>2</sup> Rubber  
 - Cable/Electrode Holder 4m 25mm<sup>2</sup> Rubber  
 Cod. 602060000L



**STEL BAG**  
 Portable and easy to use the Max can be used by anyone...anywhere!  
 Cod. 6011410000



**TIG TORCH 26V**  
 Tig Torch with Valve.  
 Cod. 642850000L 4m Air  
 Cod. 600967000L 8m Air



**CAD RC1**  
 Remote Control + Cable  
 Cod. 600015000L Remote Control  
 Cod. 600026000L 10m Cable