

















CE CERT.









The Inverter Welding Power Source TIG dp 181H developed by STEL concentrates excellent weld performance in both DC TIG welding with high frequency ignition, and Stickelectrode welding, The newly engineered design has resulted in a portable lightweight DC TIG machine of compact dimensions.

The advanced technology of the powerful microprocessor results in a perfect arc ignition every time.

MADE IN ITALY




MAIN FEATURES



DIGITAL DISPLAY

Digital Display for a clear and easy reading of the parameters at any time.



HIGH FREQUENCY

HF (High Frequency) ignition, slope up and slope down adjustment (from 0 to 10s) for a perfect crater filler.



DC PULSING

In addition to to the many functions featured, the operator is also able to TIG PULSE resulting in optimum arc formation with regulated and lower heat input, ideal for welding thin gauge materials.



ARC FORCE/HOT START

In STICK Mode you can use:

- -Hot Start 0/50% of the Welding Current.
- -Arc Force 0/50% of the Welding Current.



PRINCIPLE FEATURES

Principal features include: TIG DC welding (2T, 4T), Pulsing, pre-gas and post-gas time adjustment, variable slope up and down, Tig lift, digital display of all welding parameters, low energy consumption, VRD, TIG Torch with up/down regulation.





Technical Data	TIG dp 181H
Main Voltage	230/240 V
Phase	1
Frequency	50/60 Hz
Real Current (20%)	13,5 A
Real Power (20%)	3 KVA
Power Factor	0,7
No Load Voltage	95 V
Current Range	4-180 A
Welding Current 30% (25°C)	180 A
Welding Current 100% (25°C)	120 A
Welding Current 20% (40°C)	180 A
Welding Current 60% (40°C)	115 A
Welding Current 100% (40°C)	105 A

Features	TIG dp 181H
Earth Clamp	25 mm ²
Degree of Protection	IP 23
Insulation Class	Н
Cooling	Air
Work Temperature	40°C
Length/Width/Height (mm)	440x160x340
Weight	9,5 Kg

The date is measured at an environment temperature of 40 $^{\circ}\text{C}$

Main Accesories:



TIG TORCH

- Tig Torch 17 4m Air Cod. 609910000L
- Tig Torch 17 8m Air Cod. 600972000L
- Tig Torch 26 4m Air Cod. 609920000L
- Tig Torch 26 8m Air Cod. 600973000L



GAS REGULATOR WITH FLOWMETER
Gas Regulator with Flow Meter for a
perfect and safe gas regulation (italian gas
connection).

Cod. 6056100000



HELMET MEGA 600S

Large viewing area for maximun vision featuring innovative adjustments of delay, sensitivity and DIN protection, Shade 9-13 Cod. 601253000L



CAD RC1

cod. 600571000L

- cod. 600572000L Cavo 10m
- cod. 600573000L Cavo 20m
- cod. 600574000L Cavo 30m



SHOULDER STRAP KIT

Pratical shoulder strap, designed for comfortable carrying of the welding power source.

Cod. 600376000L